







CaptureVision System

Lumens CaptureVision System LC200 is an innovative media processor that allows you to record and create live streaming by mixing, encoding, and switching up to 4 HDMI or 3 IP video sources, and 4 audio sources. The LC200 can backup video files to a content management server or stream to most cloud video servers. It is applicable for use in education, corporate, government, healthcare, house of worship, and other applications.

Key Features

- Supports 1080p 60/30fps recording.
- Supports 4 HDMI Inputs and IP video sources including Lumens IP Cameras, and standard RTSP streams.
- Flexible scaling and window processing, supports PIP, PBP and up to 4 windows layout and mixing.
- Advanced Scenes Switch.
- Supports HDMI-embedded audio or analog stereo audio with 4 channels Audio Input mixing and gain control.
- Built-in 1TB HDD storage.

Supports 4 full HD HDM

HDMI-embedded audio.

video inputs and

One Program(mixed video)

and one Multi-view(GUI)

interface output to display.

Supports USB Mouse

interface operations.

and Keyboard for the GUI

Product Interface



Supports USB Mouse

interface operations.

and Keyboard for the GUI

Ethernet port allows to receive video streaming from the IP

source, stream transport and transfer storage directories

It also supports embedded web interface and AV control

systems

Product Specifications

	VIDEO INPUT	
Number/Signal	4 HDMI digital video	Number/Signal
Connection	4 female HDMI type-A	
Resolution Range	480i~1080p 60fps	
IP Source	Lumens IP PTZ / Box Cameras RTSP Source (H.264 1080p 60 / 30fps)	USB
١	002	
Video Compression	H.264 / AVC 4:2:0 8bit color Encoding profile: High, Main, Baseline	Serial Control
Bitrate	200 kbps to 10 Mbps	Ethernet Host P
	VIDEO OUTPUT	
Number/Signal	3 H.264 / AVC digital video over Ethernet 2 HDMI digital video	Streaming Protocol
Scaled Resolution	1080p	
Frame Rate	30 / 60 fps	
REC	ORDING AND STORAGE	Support IP Sour
Internal Storage	Standard 1TB HDD / Optional 2TB HDD	Scenes Switch
External Storage	1 USB 3.0 port in front panel	
File Type	MP4 (H.264 / AAC), JPEG	Layout Switch
Resolution	360p, 720p, 1080p	Background Sw
Frame Rate	Max. 1080p 60 / 30 fps	Overlay
	AUDIO INPUT	File Backup
	4 Line In/MIC In (stereo, 3.5mm phone jack)	
Number/Signal	4 stereo, digital de-embedded audio	Power Supply
	from HDMI IP Audio Source	Power Consum
	(RTSP, AAC-Raw, 16K/44.1K/48K)	Dimension
	AUDIO PROCESSING	Dimension
Compression	AAC-LC	Weight

AUDIO OUTPUT		
Number/Signal	1 stereo, unbalanced 3.5mm phone jack 2 stereo, digital de-embedded audio from HDMI	
COMMUNICATION		
USB	2 rear panel USB 2.0 type A Support USB mouse, keyboard, HID touch display	
Serial Control	RS-232 /RS-485 port	
ETHERNET		
Ethernet Host Port	1 female RJ-45 10/1001000 Base-T high/full duplex	
Streaming Protocol	Pull: RTSP Push: RTMP / RTMPS / MPEG-TS TCP, UDP, HTTP DHCP Client	
FUNCTIONS		
Support IP Sources	Lumens IP Camera, RTSP	
Scenes Switch	Yes, preset for layout, background, and overlay	
Layout Switch	Yes (Single, PIP, PBP, 3 and 4 windows layouts)	
Background Switch	Yes	
Overlay	Yes	
File Backup	FTP / SFTP / USB Flash Drive	
GENERAL		
Power Supply	DC In , 12V / 2A	
Power Consumption	24W	
Dimension	Standard 1u rack dimensions 122.5mm(L) x 431mm (W) x 44.3mm (H)	
Weight	1.2 kg	

Optional Accessory

Lumens LC-RC01 remote control panel, a wall plate for the LC200 to control the live streaming, recording, and video file saving options. The panel provides three macro functions that can remotely switch the scene and control the cameras preset. The LC-RC01 can be extended to 30 meters through a Cat 5e cable. It can be mounted on walls and furniture in any standard one-gang US/EU A/V frame enclosure. Equipped with a USB port, it supports USB flash drives to record or backup video files. The LC-RC01 offers greater flexibility for operating the LC200.



U.S. standard: LC-RC01U



Europe standard: LC-RC01E



Lumens Integration, Inc. 4116 Clipper Court Fremont, CA, 94538 Phone: +1-866-600-0988 Fax: +1-510-252-1389 Lumens Europe De Nayerstraat 17 9470 Denderleeuw Belgium Phone: +32-473-58-38-95 Fax: +32-2-452-76-00



www.MyLumens.com