LC200

CaptureVision Station





- Supports 1080p 60/30fps video recording.
- Supports 4 HDMI Inputs and IP video sources including Lumens IP cameras, and standard RTSP streams.
- Flexible scaling and window processing, supports PIP, PBP and up to 4 windows layout and mixing.
- · Advanced Scenes Switch.
- Supports HDMI-embedded audio or analog stereo audio with 4 channels Audio Input mixing and gain control.
- Built-in 1TB HDD storage.



Introduction

Previously, we used to go to the auditorium, amphitheater, and concert hall to enjoy a symphony, an opera, or a sports event. We had to attend a live performance physically; otherwise, we would miss our favorite play or show and had to wait for a while until the next tour came to town. With the rapid development of the Internet and A/V technology, new forms of media are springing up. From video presentation, corporate meetings, to a religious sermon, streaming and recording have removed the geographical distance and become the way organizations distribute video content. Lots of possibilities and opportunities are created; however, it also complicates the A/V system.

Streaming and recording require ease of use and managment:

Too much technology complexes the streaming process. One A/V system must be compatible with different video sources and multiple streaming protocols. Streaming and recording configurations must be easy to setup. Recording files should be manageable and flexible to store in a variety of locations.

Live production capability:

Today viewers get bored quickly by watching the same shot even for a short period. The constant change of layouts, overlay, and background the increase audience engagement and enhance viewer experience.



Lumens media processor Capture Vision Station:

The LC200 is an H.264 encoder that integrates functions of streaming, recording, switching, and live production. From content laptops to Lumens IP cameras, the LC200 can process and mix four channels at one time. The ability to stream and records simultaneously at different configuration makes the LC200 the perfect A/V product for video presentations. Recording files can be stored in the builtin 1TB hard drive, external USB storage or uploading to partner servers like Panopto, Kaltura, Opencast, etc.

Easy to use and manage:

The LC200 can be managed through the front panel, user-friendly director GUI, and webpage configurations and director. Only a little training is needed. No technical background or previous experience is required.

Advanced scenes switching with multicameras controller: The LC200 supports user-defined layout, title/ logo overlay, and background. An advanced scene is a combination of the above effect that predefined by users which allow quick switching. Live production capability attracts the audience, guild their understanding, and enhance their takeaway.

Benefits from streaming and recording:

The LC200 can be used in many professional situations. With professional A/V source equipment, corporations can live streaming an event or record training material. Educational instituions can capture lectures for those students who are unable to attend classes. Religious institutions can live streaming sermon to spread ministry all over the world, and record services and preserve a wealth of knowledge.


Applications:

- Corporate
- **Events**
- Education
- eSports
- Government
- House of Worship
- Healthcare

Features

4-Channel recording, streaming, live switching media processor

Lumens LC200 CaptureVision Station is an all-in-one media processor. Just one stand-alone device that allows you to mix four video sources, recording, streaming, and live-switching simultaneously; perfect to serve as the core system for your video project.



Bring multiple videos and audio together

The LC200 captures various video sources, including HDMI inputs, Lumens IP cameras, and RTSP streams, and allows you to switch among them. Together with four line-in / MIC-in inputs, you can provide complete audiovisual experience to your viewers!



Record everything

The LC200 records not just the program-out video but also records four independent channels video as well with gorgeous high definition images and crystal clear audio, which also makes your post-production much easier.



Built-in 1TB HDD, USB port, FTP supports

The LC200 has a built-in 1Terabyte hard drive that can store up to 500 hours of video. You also have options to upload your recordings to an external USB device or the FTP server.



Live advanced scenes switch

The powerful function of advanced scenes switch, helps you capture the attention of your viewers and increase audience engagement in your event. By iust one click, vou can roll out user-defined scenes that contain PBP PIP layout, title/logo overlays, and pleasing background.



Scheduling

Through Outlook or Google calendar, you can schedule your important events to create, record and stream your video content.



Content management system integration

The LC200 integrates with several content management systems like Panopto, Kaltura, and Opencast, etc. which are great applications for enterprise video and school lectures.



Multi-stream anywhere

Live streaming is a powerful tool. The LC200 can live stream up to three destinations like YouTube, Facebook, Twitter or twitch.



vMix












WOWZA



Overview

Front panel



Rear panel

(3.5 mm phone jack)

For line in and MIC in.



Supports Support 4 full HD HDMI video inputs And HDMI-embedded audio

Line Out

3.5mm phone jack line out for

HDMI Output x2 One Program(mixed video) And one Multi-view(GUI) interface output to display

From the A/V Control and manage the LC200 from A/V control system

Application

AUDIO/VIDEO STREAMING AND RECORDING

The LC200 can serve as the central switching and processing device for an A/V system. This system uses the LC200 to manage A/V sources and records IP cameras or sources, together with a PC or laptop source connected through HDMI.

Only need an HDMI display and USB mouse, user can switch the A/V source, different layout, background and overlay during a recording session.

Lumens camera controller is able to control cameras to the appropriate position or set the presets to help move quickly with a PTZ cameras.

Users have the option to save MP4 files directly to a USB thumb drive or the built-in HDD in LC200.

In addition to video recording, the LC200 can also stream live to cloud platforms such as Youtube, Facebook, Wowza, Microsoft Stream, etc.

Cameras IP Controller IP Cameas Source Live Streaming Content Delivery Networks VC-AS0P VC-BC601P VC-BC6


LECTURE RECORDING AND DISTANCE LEARNING

The LC200 can record the content from a presenter's computer(PPT, etc.) and the video from cameras in the classroom, and mix all the audio or microphone inputs.

With scheduling, system administrators will avoid missing important classroom recordings.

The presenter can start or stop recording with a remote control panel.

The LC200 supports Content Management System like Panopto, Kaltura, OpenCast, and FTP. After video recording, the LC200 will automatically upload the video files to the content management server. Students who are not participating in this course can go to the Content Management System for further review.



Optional Accessory


LC-RC01 Remote Control Panel

Lumens LC-RC01 remote control panel, a wall plate for the LC200 to control the live streaming, recording, and video file saving options. The panel provides three macro functions that can remotely switch the scene and control the cameras preset.

The LC-RC01 can be extended to 30 meters through a Cat 5e cable. It can be mounted on walls and furniture in any standard one-gang US/EU A/V frame enclosure. Equipped with a USB port, it supports USB flash drives to record or backup video files. The LC-RC01 offers greater flexibility for operating the LC200.



U.S. standard: LC-RC01U Europe standard: LC-RC01E



	VIDEO INPUT		
Number/Signal	4 HDMI digital video		
Connection	4 female HDMI type-A		
Resolution Range	480i~1080p 60fps		
IP Source	Lumens IP PTZ / Box Cameras RTSP Source (H.264 1080p 60/30fps)		
	VIDEO PROCESSING		
Video Compression	H.264/AVC 4:2:0 8bit color Encoding profile: High, Main, Baseline		
Bitrate	200 kbps to 10 Mbps		
VIDEO OUTPUT			
Number/Signal	3 H.264/AVC digital video over Ethernet 2 HDMI digital video		
Scaled Resolution	1080p		
Frame Rate	30 / 60 fps		
REC	CORDING AND STORAGE		
Internal Storage	1TB HDD		
External Storage	1 USB 3.0 port in front panel		
File Type	H.264 and AAC in an MP4 container, JPEG		
Resolution	480p, 720p, 1080p		
Frame Rate	Max. 1080p 60/30 fps		
AUDIO INPUT			
Number/Signal	4 Line In/MIC In (stereo, 3.5mm phone jack) 4 stereo, digital de-embedded audio from HDMI IP Audio Source (RTSP, AAC-Raw, 16K/44.1K/48K)		
	AUDIO PROCESSING		

AUDIO OUTPUT		
Number/Signal	1 stereo, unbalanced 3.5mm phone jack 2 stereo, digital de-embedded audio from HDMI	
	COMMUNICATION	
USB	2 rear panel USB 2.0 type A Supports USB mouse, keyboard	
Serial Control	RS-232 /RS-485 port	
	ETHERNET	
Ethernet Host Port	1 female RJ-45 10/100/1000 Base-T high/full duplex	
Streaming Protocol	Pull: RTSP Push: RTMP / RTMPS / MPEG-TS TCP, UDP, HTTP DHCP Client	
	FUNCTIONS	
Supports IP Sources	Lumens IP Cameras, RTSP	
Scenes Switch	Yes, preset for layout, background, and overlay	
Layout Switch	Yes,(Single, PIP, PBP, 3 and 4 windows layouts)	
Background Switch	Yes	
Overlay	Yes	
File Backup	FTP / SFTP / USB Flash Drive	
GENERAL		
Power Supply	DC In , 12 V / 2A	
Power Consumption	24W	
Dimensions	Standard 1u rack dimensions 122.5mm(L) x 431mm (W) x 44.3mm (H)	
Weight	1.2 Kg	

Accessory	LC-RC01U/E	
INTERFACE		
Button	6 LED buttons Record, Stream, Backup , Marco 1~3	
USB port	1 female USB 2.0 Type A, support USB flash drive	
EXTEND		
Cable Type	Cat 5e / Cat 6 and above	
Maximum extension Distance	30 meter (98 ft)	
MOUNTING		
LC-RC01U	Mounts to standard 1-gang US enclosures or to surfaces with included mud ring	
LC-RC01E	Mounts to standard 1-gang EU enclosures or to surfaces with included mud ring	

Accessory	LC-RC01U/E	
GENERAL		
Power Consumption	6W	
Temperature	Storage: -20 ~ + 70 °C Operating: 0 to +40 °C	
Humidity	10% to 90%	
Dimension	LC-RC01U Wallplate: 115mm (H) x 74mm (W) x 43mm (D) LC-RC01E Wallplate: 86mm (H) x 86mm (W) x 43mm (D) Receive Box: 41mm (H) x 90mm (W) x 25mm (D)	
Weight	LC-RC01U Wallplate: 0.11 Kg LC-RC01E Wallplate: 0.09 Kg Receive Box: 0.13 Kg	



Lumens Digital Optics Inc.

5F, No.20, Taiyuan St., Jhubei City 302, Taiwan TEL: +886-3-552-6255 FAX: +886-3-552-6256

Lumens Integration, Inc.

4116 Clipper Court Fremont, CA, 94538 Phone: +1-888-542-3235 FAX: +1-510-252-1389

Lumens 中国办事处

上海市浦东新区祖冲之路 1077 号 2510 室 电话:+86-21-51-098-999

传真:+86-21-50-272-210

Lumens Europe

De Nayerstraat 17 9470 Denderleeuw Belgium Phone: +32-473-58-38-95 FAX: +32-2-452-76-00